Serial No.: 10/519,569

IN THE CLAIMS

Please cancel the pending claims and substitute the following claim set:

18. (New) A method for monitoring of and fault detection in a process chain in an industrial process, said industrial process comprising at least a first sub-process (Step 12, 23, 72) having first variables (X₂) and at least one second sub-process (Step11, 21, 22, 71, 73) having second variables (X₁) arranged in a process chain, said first sub-process being performed after said second sub-process in said process chain, said method comprises the steps of:

collecting data including said second variables and calculating a multivariate sub-model based on said collected data comprising weighted averages (t11, t12, t41, t42, t5, t7, t8, t9) for said second variables for the at least one second sub-process (Step11, 21, 22, 71, 73);

receiving in the first sub-process (Step 12, 23, 72) from the at least second sub-process (Step 11, 21, 22, 71, 73) said weighted averages (t11, t12, t41, t42, t5, t7, t8, t9);

collecting data including said first variables related to the first sub-process (Step 12, 23, 72); and

calculating a multivariate sub-model for the first sub-process (Step 12, 23, 72) based on said collected data including said first variables and said weighted averages (t11, t12, t41, t42, t5, t7, t8, t9).

.

Serial No.: 10/519,569

19. (New) A method according to claim 18, **characterized** by the step of transmitting information or data related to the multivariate sub-model calculated for the first sub-process (Step 12, 23, 72) to a third sub-process (Step 13, 74).

20. (New) A method according to claim 18, **characterized** by the step of performing information or data feedback from the first sub-process (Step 12, 23, 72) to the at least one second sub-process (Step 11, 21, 22, 71, 73).

- (New) A method according to claim 18, characterized in that the data collected for each sub-process comprises process data.
- 22. (New) A method according to claim 18, **characterized** in that the step of transferring information received comprises sequential transferring of quality parameters by means of multivariate sub-model score values (t1,t2,...,tn) between the sub-processes in the process chain.
- 23. (New) A method according to claim 18, characterized in that arranging the collected data for the first sub-process (Step 12, 23, 72) in one matrix and calculating the sub-model for the first sub-process (Step 12, 23, 72) using a principal component analysis like method.

Serial No.: 10/519,569

24. (New) A method according to claim 18, **characterized** in that arranging the collected data for the first sub-process (Step 12, 23, 72) is in a first (X) and a second (Y) matrix and calculating the sub-model for the first sub-process (Step 12, 23, 72) using a PLS like method.

25. (New) A method according to claim 24, **characterized** by first matrix (X) comprises process data and the second matrix (Y) comprises quality data.

- 26. (New) A method according to claim 1, characterized by defining at least one plot, such as score plots, residual plots, residual standard deviation (DmodX) plots, contribution plots, or scaled raw data plots for the interpreting the models and occurring process faults.
- 27. (New) A method according to claim 26, characterized in that outlier detection is provided by analysis of said at least one plot.
- 28. (New) A method according to claim 18, characterized by using a number of multivariate sub-model observations comprising a prediction set to simulate the process chain.
- 29. (New) A method according to claim 18, characterized by using a number of multivariate sub-model observations comprising a prediction set to perform on-line monitoring in the process chain.

Serial No.: 10/519.569

30. (New) A first apparatus for monitoring of and fault detection in a process chain in an industrial process employing multivariate data methods, said first apparatus comprising calculating means for calculating a first multivariate sub-model for a first sub-process (Step 12, 23, 72), wherein said first apparatus comprises means for receiving from at least a second apparatus information or data related to at least a second multivariate sub-model on said collected data comprising weighted averages (t11, t12, t41, t42, t5, t7, t8, t9) for said second variables calculated for at least a second sub-process (Step11, 21, 22, 71, 73) in said industrial process and that said calculating means is arranged to calculate the first multivariate sub-model based on the information or data received from said apparatus and said second sub-process (Step11, 21, 22, 71, 73).

- 31. (New) A first apparatus according claim 30, characterized in that it comprises means for transmitting information or data to a third apparatus.
- 32. (New) An apparatus according to claim 30, characterized by means for performing information or data feedback to the second apparatus.

Serial No.: 10/519.569

33. (New) A computer program product comprising computer readable code means which, when run on a computer system, makes the computer system perform the steps according to claim 18.

- 34. (New) A computer program product according to claim 33 comprising computer readable code means which, when run on a computer system, makes the computer system perform the following additional step:
- transmitting relevant information or data to a third sub-process (Step 13, 74).